
Product data sheet





Point Laser

GPL 3 Professional



GBP 198.24*

* Price including VAT

Highly compact 3-point laser – ideal for plumb point transfer

Part number: 0 601 066 100

> More product information

Technical Data

webshop-pdp-section-technical-data-table-key-Technical data

Laser diode	635 nm, < 1 mW
Operating temperature	-10 – 40 °C
Storage temperature	-20 – 70 °C
Laser class	2
Working range	30 m
Accuracy	± 0.3 mm/m
Self-levelling range	± 5° longitudinal axis, ± 3° traverse axis
Levelling time	4 s
Dust and splash protection	IP 5X
Beam diameter	5 mm on tool
Operating time (max.)	24 h
Tripod thread	1/4", 5/8"
Projection	3 points

webshop-pdp-section-technical-data-table-key-Battery and power

Power supply	3 x 1.5 V LR6 (AA)
ababaa ada aaatiaa taabaiaa	برميا ملطمه عملا

webshop-pdp-section-technical-data-table-key-Size and weight

Weight, approx.	0.25 kg

Invented for life

Product data sheet

Power tools for trade & industry

Advantages

- Self-levelling 3-point horizontal and plumb laser for indoor
- Enables precise transfer of a reference point from the ground to the ceiling
- Easy handling due to its very compact size



